

Myers hubs

METRIC TO NPT ADAPTER – ZINC



Cat. #	Size	Unit qty.	Wt. lbs. per 100
STM 1	M20 - 1/2"	25	13
STM 2	M25 - 3/4"	25	19
STM 3	M32 - 1"	25	32
STM 4	M40 - 1 1/4"	10	40
STM 5	M50 - 1 1/2"	10	57
STM 6	M63 - 2"	10	70

Note: The Myers metric to NPT hub adapter is used to convert a threaded metric entry to an NPT entry. The female thread is NPT and the male thread is metric.

GROUND NUT – ZINC

UL File No. E-59509



Max. copper
grd. wire size

Cat. #	Size	Unit qty.	Wt. lbs. per 100	CSA [Ⓞ]	UL [Ⓞ]
STGN 1	1/2"	25	6	#8	#8
STGN 2	3/4"	25	10	#8	#8
STGN 3	1"	25	13	#8	#8
STGN 4	1 1/4"	10	15	#8	#8
STGN 5	1 1/2"	10	23	#6	#8
STGN 6	2"	10	28	#4	#8

[Ⓞ] Use of wire terminal is required by CSA and recommended by UL for wire gauges over 10 AWG.

GROUND NUT – ALUMINUM

UL File No. E-59509




Max. copper
grd. wire size

Cat. #	Size	Unit qty.	Wt. lbs. per 100	CSA [Ⓞ]	UL [Ⓞ]
STAGN 1	1/2"	25	3	#8	#8
STAGN 2	3/4"	25	4	#8	#8
STAGN 3	1"	25	6	#8	#8
STAGN 4	1 1/4"	10	8	#8	#8
STAGN 5	1 1/2"	10	11	#6	#8
STAGN 6	2"	10	14	#4	#8

[Ⓞ] Use of wire terminal is required by CSA and recommended by UL for wire gauges over 10 AWG.

CAP-OFF – ZINC

UL File No. E-23223



Cat. #	Size	Unit qty.	Wt. lbs. per 100
STC 1 [Ⓞ]	1/2"	25	13
STC 2 [Ⓞ]	3/4"	25	19
STC 3 [Ⓞ]	1"	25	28
STC 4 [Ⓞ] [Ⓞ]	1 1/4"	10	40
STC 5 [Ⓞ] [Ⓞ]	1 1/2"	10	50
STC 6 [Ⓞ] [Ⓞ]	2"	10	67

[Ⓞ] Optional nickel-chrome plate finish. Add suffix -CP.
[Ⓞ] Not UL Listed.

CAP-OFF – ALUMINUM


UL File No. E-23223



Cat. #	Size	Unit qty.	Wt. lbs. per 100
STAC 1	1/2"	25	5
STAC 2	3/4"	25	8
STAC 3	1"	25	12

NON-HAZARDOUS DRAIN PLUG – 316 STAINLESS STEEL

UL File No. E-23223



SSTS 1




SSTS 1CD

Cat. #	Size	Unit qty.	Wt. lbs. per 100
SSTS 1	1/2"	25	17
SSTS 1CD	1/2"	10	12

NON-HAZARDOUS DRAIN PLUG – ALUMINUM

UL File No. E-23223



STAC 1ST



STAC 1CD

Cat. #	Size	Unit qty.	Wt. lbs. per 100
STAC 1ST	1/2"	25	6
STAC 1CD	1/2"	25	2

Note: SSTS 1 and STAC 1ST are for knockouts and are supplied with a locknut and straight threads. SSTS 1CD and STAC 1CD are for threaded openings and are supplied without locknut and NPT threads. Not gasketed to allow for water drainage.