

# Conduit hubs

## CONDUIT HUBS – IRON SPACE-SAVER

### Applications:

- Ideal for terminating rigid/IMC conduit through the walls of enclosures
- Designed for use indoors or outdoors with rigid and IMC conduit; specific applications include: food processing plants, distilleries, breweries, sewage disposal plants, chemical plants, paper processing mills and refineries



### Features:

- Male thread is on the nut for a low profile, space saving fit
- Quick and easy when installing rigid conduit nipple between two existing enclosures
- Insulated throat provides smooth pulling surface
- Furnished with SG sealing gasket
- Hub fits standard knockouts; no special tools required

### Standard materials:

- Body and nut – malleable iron
- Sealing ring – steel and rubber

### Standard finishes:

- Body and nut – zinc electroplate
- Sealing ring – natural

### Certifications and compliances:

- UL and cUL Listed, File No. E-19189
- UL Standard 514B
- Certified by UL to CSA Standard C22.2 No. 18
- Suitable for wet locations



Conduit hubs

Cat. #	Size	Unit qty.	Wt. lbs. per 100	A	B
HUB1	1/2"	25	18	1.49	1.30
HUB2	3/4"	10	25	1.44	1.54
HUB3	1"	5	50	1.57	1.78
HUB4	1 1/4"	5	25	1.98	2.16
HUB5	1 1/2"	2	20	2.00	2.37
HUB6	2"	1	10	2.19	2.93
HUB7	2 1/2"	1	10	2.61	3.56
HUB8	3"	1	5	2.81	4.18
HUB9	3 1/2"	1	5	3.02	4.64
HUB10	4"	1	2	3.65	5.21

### Dimensions (in inches):

